# **Manhole Trench Shields**

## **MH Series**

The square manhole trench shield configuration provides the needed inside clear span while reducing the amount of excavation and restoration required. The Manhole Trench Shield is built off the same rugged frame as a 4M trench shield. Cut-outs and replaceable doors are available.

The MH Series is designed to use 5" Sch. 80 (5DS) connected spreaders which are included with the shields and provide up to 45" of vertical pipe clearance. The MH Series is suited for 40,000 lb. to 60,000 lb. excavators.



# **RMH Series**

Specially designed for personal protection during manhole installations and repair work, the Round Manhole Shields feature high strength corrugated steel walls with reinforced top and bottom rings.

Optional cut-outs and replaceable doors are available as are adjustable leg kits. Round Manhole Shields are designed to be used with rubber tired backhoes.

|                           | Size       | Pipe      | Weight | Shield     | Maximum Depth per Soil Type (ft.)* |    |      |      |  |  |  |  |  |
|---------------------------|------------|-----------|--------|------------|------------------------------------|----|------|------|--|--|--|--|--|
| Model                     | H W L      | Clearance | (lbs.) | Cap (PSF)* | Α                                  | В  | C-60 | C-80 |  |  |  |  |  |
| SINGLE-WALL               |            |           |        |            |                                    |    |      |      |  |  |  |  |  |
| MH8SW                     | 8' 8' 8'   | 45"       | 3717   | 655        | 30                                 | 19 | 15   | 12   |  |  |  |  |  |
| MH10SW                    | 8' 10' 10' | 45"       | 4270   | 426        | 21                                 | 13 | 11   | 9    |  |  |  |  |  |
| MH48SW                    | 4' 8' 8'   | N/A       | 2533   | 844        | 37                                 | 22 | 17   | 13   |  |  |  |  |  |
| MH410SW                   | 4' 10' 10' | N/A       | 2920   | 575        | 25                                 | 15 | 12   | 9    |  |  |  |  |  |
| DOUBLE-WALL               |            |           |        |            |                                    |    |      |      |  |  |  |  |  |
| MH8DW                     | 8' 8' 8'   | 45"       | 4387   | 2160       | 90                                 | 52 | 40   | 31   |  |  |  |  |  |
| MH10DW                    | 8' 10' 10' | 45"       | 5084   | 1641       | 70                                 | 40 | 31   | 25   |  |  |  |  |  |
| MH12DW                    | 8' 12' 12' | 45"       | 5781   | 1297       | 56                                 | 33 | 26   | 20   |  |  |  |  |  |
| MH48DW                    | 4' 8' 8'   | N/A       | 2866   | 2160       | 88                                 | 50 | 38   | 29   |  |  |  |  |  |
| MH410DW                   | 4' 10' 10' | N/A       | 3332   | 1813       | 75                                 | 42 | 32   | 25   |  |  |  |  |  |
| MH412DW                   | 4' 12' 12' | N/A       | 3999   | 1347       | 56                                 | 32 | 24   | 19   |  |  |  |  |  |
| DOUBLE-WALL WITH CUT-OUTS |            |           |        |            |                                    |    |      |      |  |  |  |  |  |
| MH8DW w/CO                | 8' 8' 8'   | 45"       | 4387   | 1924       | 81                                 | 47 | 36   | 28   |  |  |  |  |  |
| MH10DW w/CO               | 8' 10' 10' | 45"       | 5084   | 1252       | 54                                 | 32 | 25   | 20   |  |  |  |  |  |
| MH12DW w/CO               | 8' 12' 12' | 45"       | 5781   | 879        | 39                                 | 24 | 19   | 15   |  |  |  |  |  |
|                           |            |           |        |            |                                    |    |      |      |  |  |  |  |  |

Additional sizes are also available

#### **Optional cut-out sizes available:**

24" x 24" & 36" x 36"



| Size |  | Weight  | Shield  | Maximum Depth per Soil Type (ft.)*  |  |  |   |  |
|------|--|---|---|---|--|--|---|--|
| Dia. | Н  | (lbs.)  | Cap (PSF)*  | Α   | В  | C-60   | C-80  |  |
| 8.5' | 4'   | 920   | 1920  | 32  | 32   | 32   | 21  |  |
| 8.5' | 8'   | 1609  | 1920  | 32  | 32   | 32   | 21  |  |
| 10'  | 4'   | 1100  | 1862  | 32  | 32   | 32   | 21  |  |
| 10'  | 8'   | 1969  | 1862  | 32  | 32   | 32   | 21  |  |
| 8.5' | 8'   | 2319  | 1649  | 25  | 25   | 25   | 17  |  |
| 10'  | 8'   | 2675  | 1649  | 25  | 25   | 25   | 17  |  |
|      | Dia.<br>8.5'<br>8.5'<br>10'<br>10'<br>8.5' | 8.5' 4'<br>8.5' 8'<br>10' 4'<br>10' 8'<br>8.5' 8' | Dia. H (lbs.)   8.5' 4' 920   8.5' 8' 1609   10' 4' 1100   10' 8' 1969   8.5' 8' 2319   10' 8' 2675 | Dia. H Cap (PSF)*   8.5' 4' 920 1920   8.5' 8' 1609 1920   10' 4' 1100 1862   10' 8' 1969 1862   8.5' 8' 2319 1649   10' 8' 2675 1649 | Dia. H (lbs.) Cap (PSF)* A   8.5' 4' 920 1920 32   8.5' 8' 1609 1920 32   10' 4' 1100 1862 32   10' 8' 1969 1862 32   8.5' 8' 2319 1649 25 | Dia. H (lbs.) Cap (PSF)* A B   8.5' 4' 920 1920 32 32   8.5' 8' 1609 1920 32 32   10' 4' 1100 1862 32 32   10' 8' 1969 1862 32 32   8.5' 8' 2319 1649 25 25   10' 8' 2675 1649 25 25 | Dia. H (lbs.) Cap (PSF)* A B C-60   8.5' 4' 920 1920 32 32 32   8.5' 8' 1609 1920 32 32 32   10' 4' 1100 1862 32 32 32   10' 8' 1969 1862 32 32 32   8.5' 8' 2319 1649 25 25 25   10' 8' 2675 1649 25 25 25 |  |

## Optional Replaceable cut-out (RC) sizes:

RMH 8.5 x 8 w/RC - Two (2) 55"w x 40"h, One (1) 29"w x 24"h RMH 10 x 8 w/RC - Two (2) 72"w x 48"h, One (1) 41"w x 30"h